Product Information

DE-F919

Material description:	paper, white, wood-free, one-side coated, semi-glossy appearance; provides high colour contrasts and features high level of opacity; approved for direct contact with dry, moist, non-fatty accuracy
Applications:	multi-purpose label, particularly useful for high-end, multicolour labels requiring not only high level of contrast but also high level of register accuracy
Label stock thickness:	70 µm, 80 g/m²
Adhesive:	CS2: rubber based, hot-melt adhesive
Adhesive thickness:	standard adhesion, good initial tack
Adhesion power:	initial tack: 12,0 N FTM 9
Liner:	glassine paper, surface-sized
Liner thickness:	53 µm, 60 g/m²
Temperature range:	- 40 °C to + 60 °C
Application temperature:	> + °C
Print method:	thermal transfer print, silk screen printing, flexographic printing, offset printing
Ribbon recommendation:	DE-R21, DE-R58
Shelf life:	2 years at max. +20 ° C and 50 % relative humidity

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.0

create date 2020-03-25