Produktinformation

DE-F809

Material description:	PVC film, translucent, matt finish; excellent resistance to light and ageing; suitable for outdoor use
Applications:	Self-laminating cable markers with partial white print-on area
Label stock thickness:	80 µm
Adhesive:	AS2: acrylic adhesive, solvent-based
Adhesion:	permanent haftend
Klebkraft:	Glass: 10 N/25 mm FTM1
Web material:	kraft paper
Web material thickness:	135 g/m²
Temperature range:	- 30 °C bis + 90 °C
Application temperature:	> + 5 °C
Print method:	thermal transfer, silk screen printing
Recommended ribbon:	DE-R99, DE-R25

Solvent resistance:

Solvent	Reaction time	Result
benzine	10 minutes	no bulge
diesel	10 minutes	no influence
engine oil	10 minutes	no objection
hydraulic oil	1 hour	no objection
salt spray	24 hours	no unfluence

Shelf life: 2 years at max. +22 °C and 50 % r.h.

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.3

create day 2021-07-21