Product Information

DE-F356

Material description:	thermal transfer printable polyethylene film, white, destructible, permanent adhesive; UL registration MH48716*)
Application:	self-destructive security label
Material thickness:	52 µm
Adhesive:	permanent pressure sensitive rubber base adhesive
Adhesive thickness:	21 – 24 µm
Adhesion:	stainless steel: film ruptures during adhesion test acrylic: film ruptures during adhesion test glass: film ruptures during adhesion test
Web material:	glassine paper
Web material thickness:	56 µm
Temperature range:	- 40 ° C up to + 80 ° C
Adhesion temperature:	> + 10 °C
Print methods:	thermal transfer
Ribbon recommendation:	DE-R25*), DE-R22*), DE-R18*), DE-R19*), DE-R41*)
Storage:	2 years at max. + 21 ° C and 50 % r. h.
	*) UL recognized component

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.5

creation date: 2018-11-19