Product Information

DE-F900

Material description:	woodfree, supercalendered paper, white, matte surface, excellent low-temperature performance, approved for direct contact with dry and moist, non-greasy foodstuffs
Application:	on all common substrates, including apolar surfaces, films, cartons, and corrugated board
Material thickness:	66 µm / 68 g/m²
Adhesive:	AW2 – permanent, acrylic adhesive, water-based
Adhesive thickness:	11 µm ± 10 %
Adhesive strength:	initial tack on glass: 15 N (FTM 9) adhesive strength 90 ° on steel: 8 N/25 mm (FTM 2)
Liner:	brown glassine liner
Liner thickness:	49 µm / 55 g/m²
Total thickness:	126 µm ± 10 %
Temperature range:	- 20 ° C - + 80 ° C
Application temperature:	> + 5 ° C
Printing methods:	thermal transfer, flexographic printing, offset printing
Recommended Ribbon:	DE-R21, DE-R58 (each on unprinted material surface)
Shelf life:	2 years at max. 20 – 25 ° C and 40 – 50 % relative humidity without direct exposure to sunlight

Important Note:
All above-mentioned data are based on our most up-to-date knowledge and experience and intended for information purposes only. They do not represent any guarantee. All materials are being sold subject to the buyer's prior verification of their suitability for the intended application. This product information sheet replaces all earlier versions. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Phone: +49 8153 9096-0 • e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Registry Court Munich • V1.0

Issue date: 2011-05-06