Technical Datasheet

DE-F412

Material description:	PVC, transparent, matt Material strength: 80 µm
Application:	Identification in external areas, protection film, cable marker
Adhesive:	description: permanent quality: acrylate strength: 20-23 µm
Liner:	strength: 81 µm weight: 75 g/m²
Temperature range:	-40 °C to +80 °C
Application temperature:	> +10°C
Adhesion:	initial adhesion: 380 N/m On steel: 726 N/m FTM 1 On glas: 682 N/m FTM 1
Printing types:	flexo-printing, thermotransfer-printing
Ribbon recommendation:	DE-R89
Storage:	approx. 2 years at 21°C and 50% relative air humidity

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This technical information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.1

Erstelldatum 29.02.2008 08:36:00