Product Information

DE-F205

Material description:	White, woodfree, machine-coated, midgloss paper; material provides high degree of print contrast and high level of opacity; for application on dry, as well as humid, non-fatty food;
Application:	Universal label paper for quality multicolour labels requiring high contrast and fine printing detail
Label stock thickness:	70 µm, 80 g/m²
Adhesive:	AW2: acrylic adhesive, water based
Adhesion:	standard adhesive Initial tack: 14,0 N FTM 9
Liner:	glassine paper, surface-sized
Liner thickness:	53 µm, 60 g/m²
Temperature range:	- 20 ° C to + 80 ° C
Application temperature:	> 0 °C
Print method:	thermal transfer, screen, flexography, offset
Ribbon recommendation:	DE-R21, DE-R58 (on unprinted material surface)
Shelf life:	2 years at max. 20-25 °C and 40-50% relative humidity without direct exposure to sun/moisture (Failure to comply with the conditions may result in material deformation and processing problems)

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.5

create date 2021-04-01