Product Information

DE-F410

Material description:	A gloss white polyester film with print treated surface for enhanced ink adhesion.
Applications:	"Transfer PET White PT" was specifically developed for durable applications, for example labels on white goods or electronic equipment. The glossy, smooth surface is print treated and can be thermal transfer printed. Best results can be obtained with resin ribbons. This material can be used to label Durable Goods with a high and medium surface energy, for example metals and plastics like ABS and Polycarbonate. Labelling of rough substrates is not recommended.
Label stock thickness:	50 µm
Adhesive:	AW2: acrylate, water-based
Adhesion:	normally sticky
Adhesion power:	Initial Tack: 14 N/25 mm FTM 9 Glass Peel Adhesion 90°: 7,5 N/25 mm FTM 2 st. st. 24h
Liner:	glassine paper
Liner thickness:	57 µm
Temperature range:	- 40 °C to 150 °C
Application temperature:	> 5 °C
Print method:	thermal transfer, flexo, silkscreen
Ribbon recommendation:	DE-R22, DE-R99
Shelf life:	2 years at 22 ° C and 50 % relative humidity

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.1

create date 2018-03-23