Product Information

DE-F387

Material description:	Polyethylene film, glossy white with a pressure-coated top coat for excellent color anchoring; UV and weather resistant; approved for direct contact with dry and moist, non-greasy food
Applications:	versatile, especially suitable for labeling squeeze bottles or other flexible containers
Label stock thickness:	82 µm, 81 g/m²
Adhesive:	AW2: acrylic adhesive, water-based
Adhesion:	permanent adhesive
Adhesion power:	initial tack: Glass: 10 N FTM9 Adhesive strength 90°: St.steel: 6 N/25 mm FTM2
Liner:	white glassine-paper
Liner thickness:	54 µm, 61 g/m²
Temperature range:	- 20 °C to + 80 °C
Application temperature:	> +5 °C
Print method:	Flexographic printing, screen printing, offset printing, gravure printing, thermal transfer printing
Ribbon recommendation:	DE-R88, DE-R85 (in each case on unprinted material surface)
Shelf life:	2 years at max. 20-25 °C and 40-50 % r.h. without direct insolation

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.6

create date 2019-05-20