Product information

DE-F408

Material description:	Thermal transfer printable polyester film, silver, matte;
Applications:	automotive and electronics industry for outdoor use or nameplates
Label stock thickness:	60 µm; 75 g/m²
Adhesive:	AS3: Acrylatkleber, solvent based
Adhesion:	strong adhesive
Adhesion power:	Stainless steel: 16 N/25 mm FTM1
Liner:	glassine paper
Liner thickness:	57 µm; 65 g/m²
Temperature range:	- 40 °C bis + 150 °C
Application temperature:	> + 0 °C
Print method:	thermal transfer
Ribbon recommendation:	DE-R22, DE-R89 (in each case on unprinted material surface)
Shelf life:	2 years at +20-25°C and 40-50% r.h. without direct insolation

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.2

create date: 22.06.2021