Product Information

DE-F660

Material description:	polyethylene, white, matte, with paper-like topcoat; excellent printability, top tack even if contact between adhesive and surface is only punctual
Applications:	for challenging applications and uneven surfaces, highly recommended for shrink-wrapped pallets, wood, rough metals or synthetic surfaces
Label stock thickness:	110 µm ±10%, 90 g/m² ±10%
Adhesive:	CS4: solvent based rubber adhesive
Adhesive thickness:	31 µm, 30 g/m²
Adhesion:	very strong adhesive
Adhesion power:	initial adhesion / glass: 33 N/25 mm FTM 9 stainless steel: 17 N/25 mm FTM 2
Liner:	supercalendered glassine paper
Liner thickness:	56 µm, 62 g/m²
Temperature range:	- 40 °C to + 70 °C
Application temperature:	> - 5 °C
Print method:	thermal transfer, flexo printing, screen printing and letterpress printing
Ribbon recommendation:	DE-R25, DE-R89
Shelf life:	1 year at 22 °C and 45 % relative humidity without direct insolation (In case of non-compliance of conditions the consequence will be adhesive adherence which might entail problems in processing the labels)

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.2

create date 2018-05-02