Product Information

DE-F432

Description of the material:	Polyester, white, matt; high resistance to UV, temperature and chemicals
Applications:	very good adhesion to high-energy substrates; very good printability in thermal transfer printing; not suitable for fan-fold
Label stock thickness:	55 µm, 74 g/m²
Adhesive:	Acrylate, solvent-based
Adhesive thickness:	24 g/m²
Adhesion:	permanently adhesive
Adhesion:	Initial liability: 9 N FTM 9 Glas Peel strength at 90°: 12 N/25mm FTM 2 Stahl 24h
Liner:	Glassine
Liner thickness:	57 µm, 64 g/m²
Temperature range:	- 80 °C bis + 150 °C
Verklebetemperatur:	> + 0 °C
Print methode:	Flexographic, screen and thermal transfer
Ribbon recommendation:	Wax/resin ribbon
Shelf life:	2 years at a maximum of 22°C and 50% relative humidity

Wichtiger Hinweis:
Die oben genannten Angaben basieren auf dem gegenwärtigen Stand unserer Erfahrungen. Sie verstehen sich ausschließlich als Information und stellen keine Garantie dar. Alle Materialien werden unter dem Vorbehalt geliefert, dass der Besteller sich vor Gebrauch von der Eignung und Beschaffenheit für den jeweiligen Einsatzzweck überzeugt.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.0

Date created: 12 July 2012