Product Information

DE-F809G

Material description:	PVC-film, transparent matte; good resistance to light and chemicals; suitable for outdoor use
Applications:	Self-laminating cable markers with partial white print-on area
Label stock thickness:	90 µm
Adhesive:	AW3: Acrylate adhesive, water-based
Adhesion:	strong permanently adhesive
Adhesion power:	Glass: 18 N/25 mm FTM1
Liner:	Glassine paper
Liner thickness:	62 µm 72 g/m²
Temperature range:	- 30 °C to + 90 °C
Application temperature:	> +10 °C
Print method:	thermal transfer printable, silk screen printing
Ribbon recommendation:	DE-R99, DE-R25
Shelf life:	2 years at a maximum temperature of 20–25 °C and 40–50% relative humidity

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control, we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.4

create date 2026-05-15