Produkt Information

DE-F 914

Material description:	Paper, wood-free, semi-glossy, white, good low-temperature qualities, for direct contact with dry, humid and slightly greasy food, approval according to 1935/2004/EC and FDA § 175.105.
Application:	Identification on all common substrates
Material thickness:	69 µm, 80 g/m²
Adhesive:	AS3: solvent-based acrylic adhesive, permanent
Adhesion:	Strong adhesion Initial tack: 16N/mm FTM 9 glass Peel adhesion: 9N/mm FTM 2 steel
Web material:	calendered glassine paper
Web thickness:	51 µm, 57 g/m²
Temperature range:	- 20 ° C up to + 80 ° C
Application temperature:	0 > + ° C
Print methods:	Thermal transfer print, flexographic printing, offset printing, and silk-screen printing
Storage:	2 years at max. + 22 ° C and 45 % r. h.

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all former versions. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Woerthsee • phone: +49 (0) 8153/9096-0 • facsimile: +49 (0) 8153/9096-96 Email: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Court Munich • V1.0

Issue date 2016-5-19