**Product Information**

**DE-F175**

| | |
|---|---|
| **Material description:** | Polyester film, white, glossy, smear and scratch resistant, weather-resistant |
| **Applications:** | automotive and electronics industry |
| **Label stock thickness:** | 50 µm ±10 % |
| **Adhesive:** | AS3: Acrylic adhesive, solvent-based, temperature sensitive |
| **Adhesive thickness:** | 22 µm ± 3 % |
| **Adhesion:** | strong permanent adhesive |
| **Adhesion power:** | Glass: 19 N/25 mm FTM1 72h<br>Acryl: 20 N/25 mm FTM1 72h<br>Stainless steel: 18 N/25 mm FTM1 72h<br>Polypropylen: 15 N/25 mm FTM1 72h |
| **Liner:** | Glassine |
| **Liner thickness:** | 56 µm ± 10 % |
| **Temperature range:** | - 40 °C to + 150 °C |
| **Application temperature:** | > + 2 °C |
| **Print method:** | thermal transfer, flexo, screen printing |
| **Ribbon recommendation:** | DE-R89 |
| **Shelf life:** | 2 years at max. + 20 °C – 25 °C and 40 % - 50 % r.h. without direct insolation (in case of non-compliance of conditions the consequence could be adhesive adherence which might entail problems in processing the labels) |

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

**Dynamic Systems GmbH** • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.3

create date 2020-06-15