Product Information

DE-F907

Material description:	thermal transfer paper, white, coated, wood-free; ideal for low temperatures; approved for direct contact with dry and moist, non-greasy food; excellent printability with barcodes and alphanumeric data
Applications:	multi-purpose paper label for industrial and various other purposes; main areas of application are inventory and product identification labels for internal use
Label stock thickness:	69 µm, 70 g/m²
Adhesive:	AS0: general-purpose acrylic adhesive, removable
Adhesive thickness:	20 µm, 20 g/m²
Adhesion:	removable
Adhesion power:	initial tack: 3,5 N FTM 9 glass peel strength: 1,4 N/25 mm FTM 2 stainless steel
Web material:	glassine paper, calendered
Web material thickness:	53 µm, 59 g/m²
Temperature range:	- 30 °C to + 80 °C
Application temperature:	> - 15 °C
Print method:	thermal transfer printing, flexographic printing, offset printing
Ribbon recommendation:	DE-R21, DE-R58
Shelf life:	2 years at 22 °C and 50 % relative humidity

Warranty:
Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.1

create date 2017-08-31